

AMENDMENTS TO THE CLAIMS

Listing of Claims

1. (Canceled)

2. (Canceled)

3. (Currently amended) ~~The actuator of claim 2~~ An actuator for an
automated transmission in a motor vehicle drive train, comprising a central
actuating shaft with a shift finger and further comprising two sleeves supported
substantially concentrically on the actuating shaft and arranged to be driven in
mutually independent rotation about the actuating shaft, wherein two grooves
of opposite helical pitch are arranged on the actuating shaft and each of the
sleeves has at least one inward-directed guide pin engaging one of the
grooves, further comprising two motors driving the independent rotation of the
two sleeves, each of the two sleeves being driven by one of the two motors,
and further comprising two reduction gear mechanisms, each of the two gear
mechanisms being interposed between one of the two sleeves and one of the
two motors.

1 4. (Currently amended) The actuator of claim 3 4, wherein one of
2 the two grooves has a clockwise helical pitch and the other of the two grooves
3 has a counterclockwise helical pitch.

1 5. (Original) The actuator of claim 4, wherein the two grooves (40,
2 41) are arranged in adjacent axial sections of the shaft.

1 6. (Original) The actuator of claim 4, wherein at least parts of the
2 two grooves share an axial section of the shaft.

7. (Canceled)

8. (Canceled)

1 9. (Currently amended) ~~The actuator of claim 8,~~ An actuator for an
2 automated transmission in a motor vehicle drive train, comprising a central
3 actuating shaft with a shift finger and further comprising two sleeves supported
4 substantially concentrically on the actuating shaft and arranged to be driven in
5 mutually independent rotation about the actuating shaft, wherein the actuating
6 shaft comprises at least two outward-directed guide pins and each of the
7 sleeves has an internal groove, with the groove of one of the sleeves having
8 an opposite helical pitch from the groove of the other sleeve, and wherein one
9 of said guide pins engages the groove in one of the sleeves and the other of
10 the guide pins engages the groove in the other of the sleeves, further
11 comprising two motors driving the independent rotation of the two sleeves,
12 each of the two sleeves being driven by one of the two motors, and further

